

CI-200A



Various power supplies

The CI-200A series can be operated with a DC adaptor, rechargeable battery or dry battery (option). The ability to use a rechargeable battery or dry battery increases portability and allows the indicator to be used in environments where little or no power is available.



FEATURES

- High strength Stainless steel housing for the crane scale
- Suitable for industrial environment
- High resolution 1/10,000 (adjustable)
- Weight back-up function
- Numeric keys & function keys
- Various power supplies [DC adaptor, Rechargeable battery or AA size dry battery x 6 (option)]
- Water splash proof protection For Crane Scale
- 2 serial ports
 - Standard: 1 port of RS-232
 - Option: 1 additional port of RS-485 (for PC, Printer, Remote display communication, etc)
- 150% overload protection for safety use
- High quality crosby shackle
- Wireless technology 70m distance
- Max. Capacity (t): 30, 50, 100



ICON



STAINLESS STEEL CASING ENCLOSURE



Light and stainless case heavy duty

HIGH CAPACITY RECHARGEABLE BATTERY



It is convenient to use and move the scale by rechargeable battery

SPECIFICATIONS

Model	Heavy Duty Wireless Crane Scale CI-200A		
Max. Capacity (t)	30	50	100
Readability (kg)	10	20	50
External resolution	1/3,000	1/2,500	1/2,000
Keys	Alpha numeric		
Function	Auto off, Resolution switch		
Display type	25mm, 6 digit ultra-luminance LED		
Operating temperature	-10°C ~ 40°C		
Power	6V /3.2Ah rechargeable Pb Battery AA		
Dimensions (mm)	330(W)x 470(D)x 1100(H)	330(W)x 470(D)x 1250(H)	330(W)x 470(D)x 1400(H)
Product weight (kg)	123	186	214