



# High Precision Balance

## FSR-B

### CHARACTERISTIC

- Four level anti-shock adjustable function
- Automatic intelligent internal CAL
- Six level adjustable function
- Weighing staticness time adjustable
- 20 Unit shield, g, ct, lb, oz, GN, dwt,....
- Built in RS232/USB Line
- Default weighing mode automatically
- Time and Date setting
- With display temperature
- With under hook
- Anti radiate, anti static metal housing and wind proof
- LCD display with backlight



### APPLICATION MODE

- Percentage weighing function
- With density Measurement
- With dynamic weighing function
- Selectable weighing and count mode
- Pricing function
- High-Low working function
- Gross/Net/Tare weight weighing function
- Peak Holding function
- Accumulate function



### SPECIFICATIONS

Item No.	Capacity (g)	Readability (g)	Repeatability (g)	Linearity (g)	Work temp (°C)	Pan size (mm)	Housing scale (mm)
FSR-B620	620	0.01	±0.01	±0.02	10~35	Ø133	295x208x305
FSR-B1200	1200	0.01	±0.01	±0.02	10~35	Ø133	295x208x305
FSR-B2200	2200	0.01	±0.03	±0.02	10~35	156x156	295x208x305
FSR-B3200	3200	0.01	±0.03	±0.02	10~35	168x168	295x208x305
FSR-B4000	4000	0.01	±0.03	±0.02	10~35	168x168	295x208x305
FSR-B6200	6200	0.01	±0.03	±0.02	10~35	168x168	295x208x305